

HDMI 2.0 4K2K Splitter series W/ SPDIF & L/R audio

Model Number: SP-H102A , SP-H104A

OVERVIEW

The Digitogo 4K2K Splitter series enables a single HDMI signal to be duplicated, and distributed across to high-resolution monitors. The HDMI input supports a resolution of up to 4K2K, as well as supporting the latest technology standards such as HDMI 2.0 and HDCP 2.2. The splitter also features multiple audio interface outputs, including HDMI audio, optical audio (S/PDIF), TOSLINK and RCA L/R audio. The device has a built-in EDID auto detector, which automatically selects the optimum resolution to support the monitors it is connected to, or allows the user to adjust it manually.

Providing crystal-clear, ultra-high definition images, Digitogo's 4K2K Splitter is a great solution for any digital signage installation, especially where impressive displays are important, such as high level events and functions.

FEATURES

- Split one HDMI signal to multiple displays
- Support HDMI 2.0 and HDCP 2.2
- Support 4K/60Hz (4:4:4) Ultra HD and 3D video
- 3 audio output options- HDMI, RCA and optical (S/PDIF)
- Independent on/off switch for RCA and optical audio
- Automatic EDID detection
- EDID manual selection available

SPECIFICATIONS

Model No.	SP-H102A	SP-H104A
Input	HDMI x 1	
Output	HDMI x 2	HDMI x 4
	SPDIF x 2	SPDIF x 4
	L/R Audio x 2	L/R Audio x 4
Resolution	Up to HDMI 3840 x2160 resolution @ 60Hz	
Supported Audio Format	Stereo Audio	
Power Supply	DC12V 2A	
Max Power Consumption	7.2W	21.6W
Video Bandwidth	25MHz - 600MHz	
Casing	Metal	
Dimensions (mm)	152 x 39 x 92	315 x 44 x 130
Net Weight	474g	1167g
Operating Temperature	0° C ~48° C	
Storage Temperature	-20° C ~ 60° C	
Relative Humidity	0~80% RH	

PACKAGE CONTENTS

- HDMI Splitter unit x 1
- Locking DC12V2A Power Adapter x 1
- AC Power Cord x 1
- Quick Installation Guide x 1

DIAGRAM

